

3rd International PFAS Congress

Paris
June 6th, 2024

Performance of Reverse Osmosis for the treatment of hazardous wastewater containing various concentrations and types of PFAS

Manon Granger-Delacroix¹, Elisabeth Geldof¹, Sébastien Georges¹, Nicolas Humez¹ and Julien Blanvillain²

¹SARPI-VEOLIA, Innovation and Processes Department, 427, route du Hazay, 78520 Limay, FRANCE.

²SEMEO, 22, Zone industrielle Le Relais, 35370 Bréal-sous-Vitré, FRANCE



NOTICE - Disclaimer

The information contained in this statement is based on the Veolia group's understanding and know-how of the scientific and technical fields discussed herein as of the time of publication. Statements that may be interpreted as predictive of future outcomes or performance should not be considered guarantees of such, but rather reasoned assessments of the possible evolution of the technologies described.

As this document is based on the state of the Veolia group's scientific, technical, and regulatory knowledge at the time of its publication, the completeness and accuracy of the information contained herein cannot be guaranteed.

Descriptions contained herein apply exclusively to those examples and/or to the general situations specifically referenced, and in no event should be considered to apply to specific scenarios without prior review and validation.

SARPI : a leading company in Europe

Treatment & valorization of
hazardous waste

10 states in Europe

+ than 110 industrials sites


+ than 10 MT treated / year




SARPI  VEOLIA

High variety of wastewaters

High variety of origins



High variety of matrices and pollutants



Challenge for the treatment of emergent pollutants by conventional technologies

Case of **PFAS**


Technologies for PFAS retention

Conventional wastewater treatment technologies are insufficient in effectively treating short-chain PFAS




	Activated carbon	IE Resin	NF	RO
Organic pollutants reduction	++	+	+++	++++
Long-chain PFAS reduction	++	++	+	++++
Short-chain PFAS reduction	-	-	-	++++
Monovalent ions reduction	-	+	-	+
Polyvalent ions reduction	-	+	++	+++
Metal load reduction	+	+	-	++

Reverse Osmosis technology



Driving force :

Pressure gradient = **TransMembrane Pressure**



Reference : Simpec

$$Retention a_j = \left(1 - \frac{[a_j]_p}{[a_j]_c} \right) \times 100$$


$[a_j]_p$ concentration of molecule a_j in permeate ($\text{ng}\cdot\text{L}^{-1}$)
 $[a_j]_c$ concentration of molecule a_j in concentrate ($\text{ng}\cdot\text{L}^{-1}$)

$$Recovery = \frac{Q_p}{Q_f} \times 100$$

Q_p flow rate of permeate ($\text{L}\cdot\text{h}^{-1}$)
 Q_f flow rate of feed solution ($\text{L}\cdot\text{h}^{-1}$)

Can we run RO with a high recovery rate to remove PFAS from pretreated hazardous wastewaters ?

Strategy



Objective :

To maximize the global recovery rate during RO

Material & methods


Mobile processing unit
designed by **SEMEO**



47 polymeric
spiral-wound membranes
for RO

2 or 3 stages
Feed-and-bleed mode

$6.8 \pm 0.2 \text{ m}^3 \cdot \text{h}^{-1}$ of feed flow rate
Ambiente temperature



Analysis

Total organic carbon
internal lab

Conductivity
internal lab

30 PFAS
external lab



Composition of feed solutions

Low-organic load


TOC

280 mg·L⁻¹

Conductivity

10 202 μS·cm⁻¹

Total PFAS

20 560 ng·L⁻¹

High-organic load


TOC

1 157 mg·L⁻¹

Conductivity

10 189 μS·cm⁻¹

Total PFAS

20 810 ng·L⁻¹

Hydraulic performances

Low-organic load

7.0 m³·h⁻¹
feed solution
flow rate

32.1 bar
transmembrane pressure
at 1st stage

6.5 m³·h⁻¹
1st stage
permeate
flow rate

93 %
recovery at 1st stage

6.2 m³·h⁻¹
2nd stage
permeate
flow rate

95 %
recovery at 2nd stage

6.1 m³·h⁻¹
3rd stage
permeate
flow rate

98 %
recovery at 3rd stage

**87 % of
Global
Recovery**

High-organic load

6.6 m³·h⁻¹
feed solution
flow rate

35.4 bar
transmembrane pressure
at 1st stage

5.8 m³·h⁻¹
1st stage
permeate
flow rate

88 %
recovery at 1st stage

5.7 m³·h⁻¹
2nd stage
permeate
flow rate

98 %
recovery at 2nd stage




**86 % of
Global
Recovery**

$$Recovery = \frac{Q_p}{Q_f} \times 100$$




Q_p flow rate of permeate (L·h⁻¹)
 Q_f flow rate of feed solution (L·h⁻¹)

Quality of the permeates

Low-organic load



High-organic load



Quality of the permeates

Low-organic load


	Feed Solution ng·L ⁻¹	Permeate Stage 1 ng·L ⁻¹	Permeate Stage 2 ng·L ⁻¹
6:2 FTS	11 000	450	< 20
PFHxA	3 400	130	< 20
PFBA	1 800	66	< 20
PFPeA	1 800	66	< 20
PFHpA	1 400	57	< 20
PFHxS	420	22	< 20
PFOS	270	< 20	< 20
PFOA	185	< 20	< 20
PFBS	140	< 20	< 20
PFPeS	120	< 20	< 20
8:2 FTS	25	< 20	< 20
Total	20 560	791	< LOQ

High-organic load

	Feed Solution ng·L ⁻¹	Permeate Stage 1 ng·L ⁻¹	Permeate Stage 2 ng·L ⁻¹
6:2 FTS	15 000	180	< 20
PFHxA	2 600	34	< 20
PFBA	1 500	< 20	< 20
PFPeA	1 000	< 20	< 20
PFHpA	200	< 20	< 20
PFOS	56	< 20	< 20
PFOA	93	< 20	< 20
6:2 FTOH	361	< 10	n.d
Total	20 810	214	< LOQ

PFAS retention

Low-organic load



$$\text{Retention } a_j = \left(1 - \frac{[a]_p}{[a]_c} \right) \times 100$$


$[a]_p$ concentration of a_j in permeate (ng·L⁻¹)
 $[a]_c$ concentration of a_j in concentrate (ng·L⁻¹)

Retention (%)

	Stage 1	Stage 2
6:2 FTS	99.5	> 99.9
PFHxA	99.5	> 99.9
PFBA	99.1	> 99.7
PFPeA	98.6	> 99.6
PFHpA	99.6	> 99.8
PFHxS	99.3	> 99.4
PFOS	> 98.2	> 98.2
PFOA	> 98.7	> 98.7
PFBS	> 98.2	> 98.2
PFPeS	> 97.6	> 97.6
8:2 FTS	> 88.2	> 88.2
Total	> 99.4	> 99.9

PFAS retention

High-organic load



Retention (%)

	Stage 1	Stage 2
6:2 FTS	99.7	> 99.9
PFHxA	99.8	> 99.9
PFBA	> 99.8	> 99.8
PFPeA	> 99.1	> 99.1
PFHpA	> 98.7	> 98.7
PFOS	> 78.5	> 78.5
PFOA	> 85.7	> 85.7
6:2 FTOH	> 99.3	> 99.3
Total	> 97.7	> 99.9

$$\text{Retention } a_j = \left(1 - \frac{[a_j]_p}{[a_j]_c} \right) \times 100$$

$[a_j]_p$ concentration of a_j in permeate (ng·L⁻¹)
 $[a_j]_c$ concentration of a_j in concentrate (ng·L⁻¹)

Quality of the permeates

Metals ($\mu\text{g}\cdot\text{L}^{-1}$)

	NF	RO
Mn	200	< 5
Cu	6.1	< 5
Al	31	6.3
Fe	68	19
Zn	34.5	7.8

Volatile compounds ($\mu\text{g}\cdot\text{L}^{-1}$)

	NF	RO
CHCl_3	21	< 1
Xylène	3	< 1

Micropollutants ($\mu\text{g}\cdot\text{L}^{-1}$)

	NF	RO
C5-C9	82	< 25
AMPA	1.2	< 0.1
Phenol	0.01	< 0.01
Diuron	0.258	< 0.05
Atrazine	0.359	< 0.025
Isoproturon	0.146	< 0.05
Glyphosate	1.1	< 0.1
Tributylphosphate	0.1	< 0.1

Take-away messages

Reverse Osmosis with a high recovery rate can be run to efficiently remove PFAS from hazardous wastewaters

Hydraulic performances

A Global Recovery up to 87 % was successfully applied on pretreated wastewater

Wastewater with a $10\text{mS}\cdot\text{cm}^{-1}$ -conductivity and a total organic carbon concentration of $1100\text{ mg}\cdot\text{L}^{-1}$ could be treated by RO

The concentrates were able to be further treated

Quality of the permeates

Both short-chain and long-chain PFAS were successfully treated

Total PFAS concentration below the limit of quantification was obtained after 2 stages of RO

In addition of PFAS, a wide range of organic micropollutants were removed

Inorganic pollutants concentration were reduced



**Merci pour votre
attention.**

**Thanks for your
attention.**